

# TUYAU ASPIRATION HELIPRENE HELIFLEX

intérieur (mm)	longueur (m)	couleur	extérieur (mm)	épaisseur (mm)	poids (kg/m)	vide (bar)	rayon de courbure (mm)
50 mm	030 m	82	53.5 mm	0.5 mm	0.27 kg	0.3 bar	50 mm
60 mm	030 m	82	64 mm	0.5 mm	0.36 kg	0.3 bar	60 mm
65 mm	030 m	82	69.2 mm	0.6 mm	0.44 kg	0.3 bar	65 mm
70 mm	030 m	82	74 mm	0.5 mm	0.42 kg	0.3 bar	70 mm
80 mm	030 m	82	84.2 mm	0.6 mm	0.48 kg	0.25 bar	80 mm
90 mm	030 m	82	94.2 mm	0.6 mm	0.7 kg	0.25 bar	90 mm
100 mm	030 m	82	104.2 mm	0.6 mm	0.6 kg	0.25 bar	100 mm
120 mm	030 m	82	124.2 mm	0.6 mm	0.67 kg	0.2 bar	120 mm
130 mm	030 m	82	134 mm	0.5 mm	0.75 kg	0.2 bar	130 mm
150 mm	030 m	82	154.8 mm	0.6 mm	1.05 kg	0.15 bar	150 mm
160 mm	015 m	82	164.8 mm	0.6 mm	1.1 kg	0.15 bar	160 mm
160 mm	030 m	82	164.8 mm	0.6 mm	1.1 kg	0.15 bar	160 mm
180 mm	015 m	82	184.8 mm	0.6 mm	1.2 kg	0.15 bar	180 mm
180 mm	030 m	82	184.8 mm	0.6 mm	1.2 kg	0.15 bar	180 mm
200 mm	010 m	82	204.8 mm	0.6 mm	1.56 kg	0.1 bar	200 mm
200 mm	020 m	82	204.8 mm	0.6 mm	1.56 kg	0.1 bar	200 mm



