



TUYAU CRISTALTEX



FLEXIBILIDADE
FLEXIBILITY



RESIST. ABRASÃO
RESISTANCE ABRASION



+55°C
-10°C
TEMPERATURA
TEMPERATURE



INTERIOR LISO
SMOOTH INTERIOR



PRESSÃO
PRESSURE



ALIMENTAR
FOOD QUALITY



ATÓXICO
NON TOXIC



RESIST. QUÍMICA
CHEMICAL RESISTANCE



ESMAGAMENTO
CRUSH
RESISTÊNCIA
RESISTANCE



intérieur (mm)	longueur (m)	couleur	extérieur (mm)	épaisseur (mm)	poids (kg/m)	pression service (bar)	pression d'éclatement (bar)
6 mm	025 m	91	11 mm	2.5 mm	0.08 kg	20 bar	60 bar
6 mm	050 m	91	11 mm	2.5 mm	0.08 kg	20 bar	60 bar
6 mm	100 m	91	11 mm	2.5 mm	0.08 kg	20 bar	60 bar
8 mm	025 m	91	13 mm	2.5 mm	0.10 kg	17 bar	55 bar
8 mm	050 m	91	13 mm	2.5 mm	0.10 kg	17 bar	55 bar
8 mm	100 m	91	13 mm	2.5 mm	0.10 kg	17 bar	55 bar
10 mm	025 m	91	15 mm	2.5 mm	0.12 kg	17 bar	55 bar
10 mm	050 m	91	15 mm	2.5 mm	0.12 kg	17 bar	55 bar
10 mm	100 m	91	15 mm	2.5 mm	0.12 kg	17 bar	55 bar
12.5 mm	025 m	91	17.5 mm	2.3 mm	0.13 kg	12 bar	35 bar
12.5 mm	050 m	91	17.5 mm	2.3 mm	0.13 kg	12 bar	35 bar
12.5 mm	100 m	91	17.5 mm	2.3 mm	0.13 kg	12 bar	35 bar
16 mm	025 m	91	21 mm	2.5 mm	0.18 kg	10 bar	30 bar
16 mm	050 m	91	21 mm	2.5 mm	0.18 kg	10 bar	30 bar
16 mm	100 m	91	21 mm	2.5 mm	0.18 kg	10 bar	30 bar
19 mm	025 m	91	25 mm	3 mm	0.26 kg	10 bar	30 bar
19 mm	050 m	91	25 mm	3 mm	0.26 kg	10 bar	30 bar
19 mm	100 m	91	25 mm	3 mm	0.26 kg	10 bar	30 bar
25 mm	025 m	91	32 mm	3.5 mm	0.39 kg	8 bar	24 bar
25 mm	050 m	91	32 mm	3.5 mm	0.39 kg	8 bar	24 bar
32 mm	025 m	91	40 mm	4 mm	0.56 kg	8 bar	24 bar
32 mm	050 m	91	40 mm	4 mm	0.56 kg	8 bar	24 bar
38 mm	025 m	91	46.4 mm	4.2 mm	0.7 kg	8 bar	24 bar
38 mm	050 m	91	46.4 mm	4.2 mm	0.7 kg	8 bar	24 bar
50 mm	025 m	91	59 mm	4.5 mm	0.95 kg	7 bar	21 bar
50 mm	050 m	91	59 mm	4.5 mm	0.95 kg	7 bar	21 bar