



TUYAU HELIFLEX SOUDURE OXY

intérieur (mm)	longueur (m)	couleur	extérieur (mm)	poids (kg/m)	pression service (bar)	pression d'éclatement (bar)
40 mm	025 m	41	42.4 mm	0.24 kg	5 bar	12.5 bar
40 mm	050 m	41	42.4 mm	0.24 kg	5 bar	12.5 bar
40 mm	100 m	41	42.4 mm	0.24 kg	5 bar	12.5 bar
50 mm	025 m	41	52.8 mm	0.30 kg	5 bar	12.5 bar
50 mm	050 m	41	52.8 mm	0.30 kg	5 bar	12.5 bar
50 mm	100 m	41	52.8 mm	0.30 kg	5 bar	12.5 bar
63 mm	025 m	41	65.4 mm	0.38 kg	4.5 bar	11.3 bar
63 mm	050 m	41	65.4 mm	0.38 kg	4.5 bar	11.3 bar
63 mm	100 m	41	65.4 mm	0.38 kg	4.5 bar	11.3 bar
70 mm	025 m	41	73 mm	0.43 kg	4.5 bar	11.3 bar
70 mm	050 m	41	73 mm	0.43 kg	4.5 bar	11.3 bar
70 mm	100 m	41	73 mm	0.43 kg	4.5 bar	11.3 bar
75 mm	025 m	41	78 mm	0.48 kg	4 bar	10 bar
75 mm	050 m	41	78 mm	0.48 kg	4 bar	10 bar
75 mm	100 m	41	78 mm	0.48 kg	4 bar	10 bar
90 mm	050 m	41	93 mm	0.59 kg	4 bar	10 bar
90 mm	100 m	41	93 mm	0.59 kg	4 bar	10 bar
103 mm	025 m	41	106.2 mm	0.69 kg	3 bar	7.5 bar
103 mm	050 m	41	106.2 mm	0.69 kg	3 bar	7.5 bar
103 mm	100 m	41	106.2 mm	0.69 kg	3 bar	7.5 bar
110 mm	050 m	41	113 mm	0.83 kg	3 bar	7.5 bar
110 mm	100 m	41	113 mm	0.83 kg	3 bar	7.5 bar
125 mm	050 m	41	128.8 mm	0.88 kg	3 bar	7.5 bar
125 mm	100 m	41	128.8 mm	0.88 kg	3 bar	7.5 bar
150 mm	050 m	41	153.8 mm	1.05 kg	3 bar	7.5 bar
150 mm	100 m	41	153.8 mm	1.05 kg	3 bar	7.5 bar



INTERIOR LISO
SMOOTH INTERIOR



TEMPERATURA
TEMPERATURE



RESIST. ABRASÃO
RESIST. ABRASION



PRESSÃO
PRESSURE



**BEST
SELLER**

