



TUYAU HELIFLEX HELISPRING



intérieur (mm)	longueur (m)	couleur	extérieur (mm)	épaisseur (mm)	poids (kg/m)	vide (bar)	rayon de courbure (mm)	pression service (bar)	pression d'éclatement (bar)
10 mm	050 m	92	16 mm	3 mm	0.18 kg	0.9 bar	35 mm	12 bar	42 bar
12 mm	050 m	92	18 mm	3 mm	0.21 kg	0.9 bar	42 mm	11.5 bar	40.3 bar
13 mm	050 m	92	19 mm	3 mm	0.23 kg	0.9 bar	45.5 mm	10 bar	38.5 bar
16 mm	025 m	92	23 mm	3.5 mm	0.3 kg	0.9 bar	56 mm	10.5 bar	36.8 bar
16 mm	050 m	92	23 mm	3.5 mm	0.3 kg	0.9 bar	56 mm	10.5 bar	36.8 bar
18 mm	050 m	92	21.5 mm	3.5 mm	0.35 kg	0.9 bar	63 mm	10.5 bar	36.8 bar
19 mm	025 m	92	26 mm	3.5 mm	0.35 kg	0.9 bar	66.5 mm	12 bar	35 bar
19 mm	050 m	92	26 mm	3.5 mm	0.35 kg	0.9 bar	66.5 mm	12 bar	35 bar
20 mm	025 m	92	27 mm	3.5 mm	0.37 kg	0.85 bar	70 mm	12 bar	35 bar
20 mm	050 m	92	27 mm	3.5 mm	0.37 kg	0.85 bar	70 mm	12 bar	35 bar
25 mm	025 m	92	34 mm	4.5 mm	0.58 kg	0.8 bar	87.5 mm	9.5 bar	33.3 bar
25 mm	050 m	92	34 mm	4.5 mm	0.58 kg	0.8 bar	87.5 mm	9.5 bar	33.3 bar
30 mm	025 m	92	39 mm	4.5 mm	0.66 kg	0.8 bar	105 mm	9 bar	31.5 bar
30 mm	050 m	92	39 mm	4.5 mm	0.66 kg	0.8 bar	105 mm	9 bar	31.5 bar
32 mm	025 m	92	41 mm	4.5 mm	0.73 kg	0.8 bar	112 mm	9 bar	31.5 bar
32 mm	050 m	92	41 mm	4.5 mm	0.73 kg	0.8 bar	112 mm	9 bar	31.5 bar
35 mm	025 m	92	45 mm	5 mm	0.88 kg	0.8 bar	122 mm	8 bar	28 bar
35 mm	050 m	92	45 mm	5 mm	0.88 kg	0.8 bar	122 mm	8 bar	28 bar
38 mm	050 m	92	49 mm	5.5 mm	1 kg				
40 mm	025 m	92	51 mm	5.5 mm	1.1 kg	0.8 bar	140 mm	7.5 bar	26.3 bar
40 mm	050 m	92	51 mm	5.5 mm	1.1 kg	0.8 bar	140 mm	7.5 bar	26.3 bar
45 mm	025 m	92	57 mm	6 mm	1.4 kg	0.8 bar	157 mm	6.5 bar	22.8 bar
45 mm	050 m	92	57 mm	6 mm	1.4 kg	0.8 bar	157 mm	6.5 bar	22.8 bar
50 mm	025 m	92	62 mm	6 mm	1.47 kg	0.8 bar	175 mm	6 bar	21 bar
50 mm	050 m	92	62 mm	6 mm	1.47 kg	0.8 bar	175 mm	6 bar	21 bar
60 mm	025 m	92	73 mm	6.5 mm	1.9 kg	0.7 bar	210 mm	5.5 bar	19.3 bar
60 mm	050 m	92	73 mm	6.5 mm	1.9 kg	0.7 bar	210 mm	5.5 bar	19.3 bar
70 mm	025 m	92	84 mm	7 mm	2.45 kg	0.6 bar	245 mm	5 bar	17.5 bar
70 mm	050 m	92	84 mm	7 mm	2.45 kg	0.6 bar	245 mm	5 bar	17.5 bar
75 mm	025 m	92	89 mm	7 mm	2.46 kg	0.6 bar	262 mm	4.5 bar	15.8 bar
75 mm	050 m	92	89 mm	7 mm	2.46 kg	0.6 bar	262 mm	4.5 bar	15.8 bar
80 mm	025 m	92	94 mm	7 mm	2.7 kg	0.6 bar	280 mm	3.5 bar	12.3 bar
80 mm	050 m	92	94 mm	7 mm	2.7 kg	0.6 bar	280 mm	3.5 bar	12.3 bar
90 mm	015 m	92	104 mm	7 mm	2.8 kg	0.6 bar	300 mm	3 bar	10.5 bar
90 mm	030 m	92	104 mm	7 mm	2.8 kg	0.6 bar	300 mm	3 bar	10.5 bar
100 mm	015 m	92	116 mm	8 mm	4.1 kg	0.6 bar	420 mm	3 bar	10.5 bar
100 mm	030 m	92	116 mm	8 mm	4.1 kg	0.6 bar	420 mm	3 bar	10.5 bar
120 mm	025 m	92	136 mm	8 mm	4.9 kg	0.6 bar	420 mm	2.5 bar	8.8 bar
120 mm	030 m	92	136 mm	8 mm	4.9 kg	0.6 bar	420 mm	2.5 bar	8.8 bar
125 mm	015 m	92	142 mm	8.5 mm	5 kg	0.6 bar	437 mm	2.5 bar	8 bar
125 mm	020 m	92	142 mm	8.5 mm	5 kg	0.6 bar	437 mm	2.5 bar	8 bar
125 mm	030 m	92	142 mm	8.5 mm	5 kg	0.6 bar	437 mm	2.5 bar	8 bar
150 mm	010 m	92	168 mm	9 mm	6.85 kg	0.5 bar	525 mm	2 bar	7 bar
150 mm	015 m	92	168 mm	9 mm	6.85 kg	0.5 bar	525 mm	2 bar	7 bar
150 mm	020 m	92	168 mm	9 mm	6.85 kg	0.5 bar	525 mm	2 bar	7 bar
150 mm	025 m	92	168 mm	9 mm	6.85 kg	0.5 bar	525 mm	2 bar	7 bar