



TUYAU HELIFLEX HYDROFLEX

| intérieur (mm) | longueur (m) | couleur | extérieur (mm) | épaisseur (mm) | poids (kg/m) | pression service (bar) |
|----------------|--------------|---------|----------------|----------------|--------------|------------------------|
| 15 mm | 025 m | 31 | 20.3 mm | 2.6 mm | 0.18 kg | 5.6 bar |
| 15 mm | 025 m | 61 | 20.3 mm | 2.6 mm | 0.18 kg | 5.6 bar |
| 15 mm | 050 m | 31 | 20.3 mm | 2.6 mm | 0.18 kg | 5.6 bar |
| 15 mm | 050 m | 61 | 20.3 mm | 2.6 mm | 0.18 kg | 5.6 bar |
| 20 mm | 025 m | 31 | 25 mm | 2.5 mm | 0.21 kg | 5.6 bar |
| 20 mm | 025 m | 61 | 25 mm | 2.5 mm | 0.21 kg | 5.6 bar |
| 20 mm | 050 m | 31 | 25 mm | 2.5 mm | 0.21 kg | 5.6 bar |
| 20 mm | 050 m | 61 | 25 mm | 2.5 mm | 0.21 kg | 5.6 bar |
| 26 mm | 025 m | 31 | 32.2 mm | 3.2 mm | 0.38 kg | 5 bar |
| 26 mm | 025 m | 61 | 32.2 mm | 3.2 mm | 0.38 kg | 5 bar |
| 26 mm | 050 m | 31 | 32.2 mm | 3.2 mm | 0.38 kg | 5 bar |
| 26 mm | 050 m | 61 | 32.2 mm | 3.2 mm | 0.38 kg | 5 bar |
| 34 mm | 025 m | 31 | 40.2 mm | 3.1 mm | 0.47 kg | 4 bar |
| 34 mm | 025 m | 61 | 40.2 mm | 3.1 mm | 0.47 kg | 4 bar |
| 34 mm | 050 m | 31 | 40.2 mm | 3.1 mm | 0.47 kg | 4 bar |
| 34 mm | 050 m | 61 | 40.2 mm | 3.1 mm | 0.47 kg | 4 bar |
| 43 mm | 025 m | 31 | 50 mm | 3.6 mm | 0.7 kg | 4 bar |
| 43 mm | 025 m | 61 | 50 mm | 3.6 mm | 0.7 kg | 4 bar |
| 43 mm | 025 m | 81 | 50 mm | 3.6 mm | 0.75 kg | 4 bar |
| 43 mm | 050 m | 31 | 50 mm | 3.6 mm | 0.7 kg | 4 bar |
| 43 mm | 050 m | 61 | 50 mm | 3.6 mm | 0.7 kg | 4 bar |
| 43 mm | 050 m | 81 | 50 mm | 3.6 mm | 0.75 kg | 4 bar |
| 55 mm | 025 m | 31 | 63.4 mm | 4.2 mm | 1 kg | 4 bar |
| 55 mm | 025 m | 61 | 63.4 mm | 4.2 mm | 1 kg | 4 bar |
| 55 mm | 025 m | 81 | 63.4 mm | 4.2 mm | 1.1 kg | 4 bar |
| 55 mm | 050 m | 31 | 63.4 mm | 4.2 mm | 1 kg | 4 bar |
| 55 mm | 050 m | 61 | 63.4 mm | 4.2 mm | 1 kg | 4 bar |
| 55 mm | 050 m | 81 | 63.4 mm | 4.2 mm | 1.1 kg | 4 bar |
| 68 mm | 025 m | 61 | 75 mm | 3.8 mm | 1.15 kg | 3 bar |
| 80 mm | 025 m | 61 | 90 mm | 5 mm | 1.95 kg | 3 bar |



 **5**
INTERIOR LISO
SMOOTH INTERIOR

+50°C
-5°C 
TEMPERATURA
TEMPERATURE

 **4**
RESIST. ABRASÃO
RESIST. ABRASION

 **4**
ESMAGAMENTO
CRUSH
RESISTÊNCIA
RESISTANCE

 **4**
VÁCUO
VACUUM


FLEXÍVEL
FLEXIBLE


**BEST
SELLER**


PRODUTO
CERTIFICADO