




TUYAU HELIFLEX MONOFLAT

intérieur (mm)	longueur (m)	couleur	extérieur (mm)	poids (kg/m)	pression service (bar)	pression d'éclatement (bar)
53 mm	100 m	51	55.8 mm	0.31 kg	6.5 bar	16.3 bar
70 mm	050 m	51	73.2 mm	0.44 kg	5.5 bar	13.8 bar
70 mm	100 m	51	73.2 mm	0.44 kg	5.5 bar	13.8 bar
78 mm	100 m	51	81.2 mm	0.48 kg	5 bar	12.5 bar
90 mm	100 m	51	93.2 mm	0.59 kg	5 bar	12.5 bar
103 mm	100 m	51	106.2 mm	0.65 kg	4 bar	10 bar
128 mm	050 m	51	131.6 mm	0.92 kg	4 bar	10 bar
128 mm	100 m	51	131.6 mm	0.92 kg	4 bar	10 bar
155 mm	050 m	51	159 mm	1.25 kg	3.5 bar	8.7 bar
155 mm	100 m	51	159 mm	1.25 kg	3.5 bar	8.7 bar



INTERIOR LISO
SMOOTH INTERIOR



TEMPERATURA
TEMPERATURE



RESIST. ABRASÃO
RESIST. ABRASION



PRESSÃO
PRESSURE



LEVE
LIGHT



FLEXÍVEL
FLEXIBLE



MONOCAMADA
MONOCAMADA