



## TUYAU HELIFLEX VENT GRIS



RESIST. ABRASÃO  
RESISTANCE ABRASION



INTERIOR LISO  
SMOOTH INTERIOR



FLEXIBILIDADE  
FLEXIBILITY



RESISTÊNCIA  
RESISTANCE



RESIST. QUÍMICA  
CHEMICAL RESISTANCE



LEVE  
LIGHT-WEIGHT



TEMPERATURA  
TEMPERATURE



VÁCUO  
VACUUM



RESIST. A FUMOS  
SMOKE RESISTANT



intérieur (mm)	longueur (m)	couleur	extérieur (mm)	épaisseur (mm)	poids (kg/m)	vide (bar)	rayon de courbure (mm)
25 mm	025 m	62	30.8 mm	0.7 mm	0.22 kg	0.5 bar	25 mm
25 mm	050 m	62	30.8 mm	0.7 mm	0.22 kg	0.5 bar	25 mm
30 mm	025 m	62	37 mm	0.8 mm	0.19 kg	0.5 bar	30 mm
30 mm	050 m	62	37 mm	0.8 mm	0.19 kg	0.5 bar	30 mm
35 mm	025 m	62	42.2 mm	0.7 mm	0.32 kg	0.5 bar	35 mm
35 mm	050 m	62	42.2 mm	0.7 mm	0.32 kg	0.5 bar	35 mm
40 mm	025 m	62	48.2 mm	0.7 mm	0.32 kg	0.5 bar	40 mm
40 mm	050 m	62	48.2 mm	0.7 mm	0.32 kg	0.5 bar	40 mm
50 mm	025 m	62	58.8 mm	0.9 mm	0.49 kg	0.45 bar	50 mm
50 mm	050 m	62	58.8 mm	0.9 mm	0.49 kg	0.45 bar	50 mm
60 mm	025 m	62	69.2 mm	0.8 mm	0.6 kg	0.4 bar	60 mm
60 mm	050 m	62	69.2 mm	0.8 mm	0.6 kg	0.4 bar	60 mm
70 mm	025 m	62	79.8 mm	0.9 mm	0.78 kg	0.4 bar	70 mm
70 mm	050 m	62	79.8 mm	0.9 mm	0.78 kg	0.4 bar	70 mm
75 mm	025 m	62	85.2 mm	0.9 mm	0.89 kg	0.4 bar	75 mm
75 mm	050 m	62	85.2 mm	0.9 mm	0.89 kg	0.4 bar	75 mm
80 mm	025 m	62	90.6 mm	1 mm	0.95 kg	0.4 bar	80 mm
80 mm	050 m	62	90.6 mm	1 mm	0.95 kg	0.4 bar	80 mm
90 mm	025 m	62	101 mm	1 mm	1.04 kg	0.4 bar	90 mm
90 mm	030 m	62	101 mm	1 mm	1.04 kg	0.4 bar	90 mm
100 mm	015 m	62	111 mm	1 mm	1.15 kg	0.4 bar	100 mm
100 mm	025 m	62	111 mm	1 mm	1.15 kg	0.4 bar	100 mm
100 mm	030 m	62	111 mm	1 mm	1.15 kg	0.4 bar	100 mm
110 mm	015 m	62	121.2 mm	1.1 mm	1.2 kg	0.33 bar	110 mm
110 mm	030 m	62	121.2 mm	1.1 mm	1.2 kg	0.33 bar	110 mm
120 mm	015 m	62	132 mm	1 mm	1.4 kg	0.33 bar	120 mm
120 mm	030 m	62	132 mm	1 mm	1.4 kg	0.33 bar	120 mm
125 mm	015 m	62	137.2 mm	1.1 mm	1.5 kg	0.3 bar	125 mm
125 mm	025 m	62	137.2 mm	1.1 mm	1.5 kg	0.3 bar	125 mm
125 mm	030 m	62	137.2 mm	1.1 mm	1.5 kg	0.3 bar	125 mm
130 mm	015 m	62	143.2 mm	1.1 mm	1.58 kg	0.3 bar	130 mm
130 mm	030 m	62	143.2 mm	1.1 mm	1.58 kg	0.3 bar	130 mm
140 mm	015 m	62	153.8 mm	1.2 mm	1.87 kg	0.3 bar	140 mm
140 mm	030 m	62	153.8 mm	1.2 mm	1.87 kg	0.3 bar	140 mm
150 mm	015 m	62	164 mm	1.2 mm	1.95 kg	0.3 bar	150 mm
150 mm	020 m	62	164 mm	1.2 mm	1.95 kg	0.3 bar	150 mm
150 mm	025 m	62	164 mm	1.2 mm	1.95 kg	0.3 bar	150 mm
150 mm	030 m	62	164 mm	1.2 mm	1.95 kg	0.3 bar	150 mm
200 mm	010 m	62	215.2 mm	1.6 mm	2.95 kg	0.25 bar	200 mm
200 mm	020 m	62	215.2 mm	1.6 mm	2.95 kg	0.25 bar	200 mm
250 mm	010 m	62	268.8 mm	2.2 mm	4.34 kg	0.2 bar	250 mm
300 mm	010 m	62	318.2 mm	2.1 mm	5.3 kg	0.15 bar	300 mm
300 mm	015 m	62	318.2 mm	2.1 mm	5.3 kg	0.15 bar	300 mm

