



TUYAU HELIFLEX VV ASP ET VENT

| intérieur (mm) | longueur (m) | couleur | extérieur (mm) | épaisseur (mm) | poids (kg/m) | vide (bar) | rayon de courbure (mm) |
|----------------|--------------|---------|----------------|----------------|--------------|------------|------------------------|
| 50 mm | 025 m | 61 | 57.5 mm | 1.1 mm | 0.47 kg | 0.45 bar | 50 mm |
| 50 mm | 050 m | 61 | 57.5 mm | 1.1 mm | 0.47 kg | 0.45 bar | 50 mm |
| 60 mm | 025 m | 61 | 68 mm | 1.1 mm | 0.52 kg | 0.4 bar | 60 mm |
| 60 mm | 050 m | 61 | 68 mm | 1.1 mm | 0.52 kg | 0.4 bar | 60 mm |
| 70 mm | 050 m | 61 | 90.5 mm | 1.2 mm | 0.71 kg | 0.4 bar | 70 mm |
| 80 mm | 025 m | 61 | 90.5 mm | 1.2 mm | 0.77 kg | 0.4 bar | 80 mm |
| 80 mm | 030 m | 61 | 90.5 mm | 1.2 mm | 0.77 kg | 0.4 bar | 80 mm |
| 80 mm | 050 m | 61 | 90.5 mm | 1.2 mm | 0.77 kg | 0.4 bar | 80 mm |
| 90 mm | 030 m | 61 | 100.6 mm | 1 mm | 0.85 kg | 0.4 bar | 90 mm |
| 100 mm | 015 m | 61 | 113.5 mm | 1.2 mm | 0.96 kg | 0.4 bar | 100 mm |
| 100 mm | 030 m | 61 | 113.5 mm | 1.2 mm | 0.96 kg | 0.4 bar | 100 mm |
| 110 mm | 030 m | 61 | 124 mm | 1.2 mm | 1.15 kg | 0.4 bar | 110 mm |
| 120 mm | 030 m | 61 | 133.5 mm | 1.2 mm | 1.22 kg | 0.33 bar | 120 mm |
| 130 mm | 030 m | 61 | 143.2 mm | 1.2 mm | 1.6 kg | 0.33 bar | 130 mm |
| 140 mm | 030 m | 61 | 154 mm | 1.2 mm | 1.64 kg | 0.33 bar | 140 mm |
| 150 mm | 015 m | 61 | 164.5 mm | 1.2 mm | 1.7 kg | 0.33 bar | 160 mm |
| 150 mm | 030 m | 61 | 164.5 mm | 1.2 mm | 1.7 kg | 0.33 bar | 160 mm |
| 160 mm | 010 m | 61 | 174.5 mm | 1.2 mm | 1.76 kg | 0.3 bar | 160 mm |
| 160 mm | 020 m | 61 | 174.5 mm | 1.2 mm | 1.76 kg | 0.3 bar | 160 mm |
| 180 mm | 020 m | 61 | 194.5 mm | 1.3 mm | 2.1 kg | 0.25 bar | 180 mm |
| 200 mm | 010 m | 61 | 214.5 mm | 1.2 mm | 2.22 kg | 0.25 bar | 200 mm |
| 200 mm | 020 m | 61 | 214.5 mm | 1.2 mm | 2.22 kg | 0.25 bar | 200 mm |
| 250 mm | 010 m | 61 | 264 mm | 1.3 mm | 3 kg | 0.2 bar | 200 mm |
| 300 mm | 010 m | 61 | 314.5 mm | 1.3 mm | 3.67 kg | 0.15 bar | 300 mm |



FLEXIBILIDADE
FLEXIBILITY



RESIST. ABRASÃO
RESISTANCE ABRASION



+55°C
-10°C
TEMPERATURA
TEMPERATURE



INTERIOR LISO
SMOOTH INTERIOR



RESISTÊNCIA
RESISTANCE



VÁCUO
VACUUM



SUPER LEVE
SUPER LIGHT



MUITO FLEXÍVEL
HIGHLY FLEXIBLE

