

TUYAU PULVERISATION HELIFLEX P80

code produit	intérieur (mm)	longueur (m)	couleur	extérieur (mm)	poids (kg/m)	pression service (bar)	pression d'éclatement (bar)
24024800805043	8 mm	050 m	43	15 mm	0.17 kg	80 bar	252 bar
24024800810043	8 mm	100 m	43	15 mm	0.17 kg	80 bar	252 bar
24024800905043	9 mm	050 m	43	16 mm	0.18 kg	80 bar	252 bar
24024800910043	9 mm	100 m	43	16 mm	0.18 kg	80 bar	252 bar
24024801005043	10 mm	050 m	43	17.4 mm	0.2 kg	80 bar	252 bar
24024801010043	10 mm	100 m	43	17.4 mm	0.2 kg	80 bar	252 bar
24024801205043	12.5 mm	050 m	43	20.5 mm	0.24 kg	80 bar	240 bar
24024801210043	12.5 mm	100 m	43	20.5 mm	0.24 kg	80 bar	240 bar

 **5**
INTERIOR LISO
 SMOOTH INTERIOR

+55°C
-10°C 
TEMPERATURA
 TEMPERATURE

 **4**
FLEXIBILIDADE
 FLEXIBILITY

 **4**
ESMAGAMENTO
CRUSH
RESISTÊNCIA
 RESISTANCE

 **5**
RESIST. ABRASÃO
 RESIST. ABRASION

80/250

PRESSÃO
 PRESSURE